

EPSTAR

EA42 Linear light - Epistar SMD 2835

Suspended linear light, modern design. Aluminium anodized / PC, incl. driver. Optional dimmable. Epistar DDM 2835 LEDs.


Technical data

LED Module producer	Epistar	Dimmable	optional dimmable
Technology	SMD 2835	Appliance class	I
Heatsink	Passive cooling	IP class	IP40
CRI	> 80	Voltage	230 V
Surge current limit	yes	Power factor (PF)	>0,90
Type	delayed switch on	System efficiency	110 Lm/W (A++)

Watt	A (mm)	B (mm)	C (mm)	Kg
14,4	632	103	23,5	0,8
21,6	932	103	23,5	1,2
28,8	1232	103	23,5	1,6
36	1532	103	23,5	1,9

Beam angle	130°
Colour temperature	830 - 840 - 850
Product colour	Aluminium anodized (Al)

DATASHEET



Life time and warranty

Warranty:	2 years
Availability of spare parts:	>10 years after last delivery
Availability for re-order :	>2 years after last delivery
Life time:	>35.000 hours (70 % light transmission)

CE Conformity

The above mentioned lights are in accordance with EU-Directives 2006/95/EC (low voltage directive), 2004/108/EC (EMC-Directive), 2009/125/EC (Ecodesign requirements) and 2011/65/EU (RoHS-directive). The standards EN55015, EN 60598, EN 61000, EN 61347 and EN 61547 have been applied.

A declaration of CE Conformity will be supplied together with the product.

Brand Inside®

With our **Brand Inside®** guarantee we guarantee as one of the few suppliers, that only brand products are inside. „What is on the packaging will be also inside!“. You will not find cloned products, "No-Name" products, B-quality, etc. from us.

Disposal

This product is in conformity with directive 2002/96/EU. Do not dispose this product with other household waste. Instead, it should be disposed at a designated collection point for the recycling of waste electrical and electronic equipment.

Limitation of liability

Subject to modifications. Please ensure you are using the latest version of this datasheet.

DATASHEET