









GT31 Track light - Cree COB

Aluminium casting, swivable, incl. driver. White, black or silver lacquered. With high performance Cree LEDs 100 Lm/Watt

For Fashion, Food, Non-Food and Pharmacy.

Technical data

LED Module producer Technology COB Heatsink CRI >83 Surge current limit ves Type

Cree Passive cooling delayed switch on

A (mm)

130

Dimmable **Appliance class** IP class Voltage Power factor (PF) **System efficiency**

Kg

1.8

not dimmable **IP40** 230 V >0.90 90 Lm/W (A+)

Beam angle

Colour temperature

Product colour

24° - 40° - 60° 830 - 840 - 850

Watt

30

Black lacquered (Bk) - Light grey lacquered (Si) - White lacquered (Wh)

B (mm) C (mm)

294

174

DATASHEET













Life time and warranty

Warranty: 2 years

Availability of spare parts: >10 years after last delivery Availability for re-order : >2 years after last delivery

Life time: >35.000 hours (70 % light transmission)

CE Conformity

The above mentioned lights are in accordance with EU-Directives 2006/95/EC (low voltage directive), 2004/108/EC (EMC-Directive), 2009/125/EC (Ecodesign requirements) and 2011/65/EU (RoHS-directive). The standards EN55015, EN 60598, EN 61000, EN 61347 and EN 61547 have been applied.

A declaration of CE Conformity will be supplied together with the product.

Brand Inside®

With our Brand Inside® guarantuee we guarantuee as one of the few suppliers, that only brand products are inside. "What is on the packaging will be also inside!". You will not find cloned products, "No-Name" products, Bquality, etc. from us.

Disposal

This product is in conformity with directive 2002/96/EU. Do not dispose this product with other houlehold waste. Instead, it should be disposed at a designated collection point for the recycling of waste electrical and electronic equipment.

Limitation of liability

Subject to modifications. Please ensure you are using the latest version of this datasheet.

DATASHEET

