











GT65 Track light - Samsung SMD 5630

Aluminium casting, swivable, incl. driver. White, black or silver lacquered, heat sink always black. With high performance Samsung LEDs 120 Lm/Watt

For Fashion, Food, Non-Food and Pharmacy.

Technical data

LED Module producer Technology Heatsink CRI Surge current limit **Type**

Samsung SMD 5630 Passive cooling >80 yes delayed switch on Dimmable **Appliance class** IP class Voltage Power factor (PF) **System efficiency**

not dimmable **IP40** 230 V >0.90 120 Lm/W (A++)

Watt A (mm) B (mm) C (mm) Kg 203 20 104 174 1,5 104 174 203 1,5 38

Beam angle Colour temperature **Product colour**

120°

830 - 840 - 860

Black lacquered (Bk) - Light grey lacquered (Si) - White lacquered (Wh)

DATASHEET













Life time and warranty

Warranty: 2 years

Availability of spare parts: >10 years after last delivery Availability for re-order : >2 years after last delivery

Life time: >35.000 hours (70 % light transmission)

CE Conformity

The above mentioned lights are in accordance with EU-Directives 2006/95/EC (low voltage directive), 2004/108/EC (EMC-Directive), 2009/125/EC (Ecodesign requirements) and 2011/65/EU (RoHS-directive). The standards EN55015, EN 60598, EN 61000, EN 61347 and EN 61547 have been applied.

A declaration of CE Conformity will be supplied together with the product.

Brand Inside®

With our Brand Inside® guarantuee we guarantuee as one of the few suppliers, that only brand products are inside. "What is on the packaging will be also inside!". You will not find cloned products, "No-Name" products, Bquality, etc. from us.

Disposal

This product is in conformity with directive 2002/96/EU. Do not dispose this product with other houlehold waste. Instead, it should be disposed at a designated collection point for the recycling of waste electrical and electronic equipment.

Limitation of liability

Subject to modifications. Please ensure you are using the latest version of this datasheet.

DATASHEET

