



KF11 Tunnel light - Samsung SMD 3030

High quality tunnel light, with aluminium casting, extreme flat, incl. Meanwell driver. These tunnel lights are suitable for indoor and outdoor applications.

Technical data

LED Module producer	Samsung	Dimmable	optional dimmable
Technology	SMD 3030	Appliance class	I
Heatsink	Passive cooling	IP class	IP65
CRI	>80	Voltage	230 V
Surge current limit	yes	Power factor (PF)	>0,90
Type	delayed switch on	System efficiency	120 Lm/W (A++)

Watt	A (mm)	B (mm)	C (mm)	Kg
50	90	315	235	3
100	180	315	235	5
150	270	315	235	6
200	360	315	235	7
300	450	315	235	9
400	540	315	235	13

Beam angle	60° - 90°
Colour temperature	830 - 840 - 860
Product colour	Black lacquered (Bk)

50 Watt: 1 Feld (Abbildung)
 100 Watt: 2 Felder
 150 Watt: 3 Felder
 200 Watt: 4 Felder
 300 Watt: 6 Felder
 400 Watt: 8 Felder

DATASHEET



Life time and warranty

Warranty:	2 years
Availability of spare parts:	>10 years after last delivery
Availability for re-order :	>2 years after last delivery
Life time:	>35.000 hours (70 % light transmission)

CE Conformity

The above mentioned lights are in accordance with EU-Directives 2006/95/EC (low voltage directive), 2004/108/EC (EMC-Directive), 2009/125/EC (Ecodesign requirements) and 2011/65/EU (RoHS-directive). The standards EN55015, EN 60598, EN 61000, EN 61347 and EN 61547 have been applied.

A declaration of CE Conformity will be supplied together with the product.

Brand Inside®

With our **Brand Inside®** guarantee we guarantee as one of the few suppliers, that only brand products are inside. „What is on the packaging will be also inside!“. You will not find cloned products, "No-Name" products, B-quality, etc. from us.

Disposal

This product is in conformity with directive 2002/96/EU. Do not dispose this product with other household waste. Instead, it should be disposed at a designated collection point for the recycling of waste electrical and electronic equipment.

Limitation of liability

Subject to modifications. Please ensure you are using the latest version of this datasheet.

DATASHEET