









EPISTAR

LM13 Filament bulb - Epistar Filament

High performance LED filament light bulb (glass). E14 socket, equivalent to 40 watt halogene. Minimum 25.000h life time.

Technical data

LED Module producer Technology Heatsink CRI Surge current limit

Type

Epistar Filament

Passive cooling

> 80 no

Dimmable Appliance class

IP class Voltage Power factor (PF)

System efficiency

not dimmable

IP20 230 V >0,90

90 Lm/W (A+)

Version Watt Kg E14 4 0,2

Beam angle **Colour temperature** Product colour

360° 827

Transparent (Tr)

DATASHEET













Life time and warranty

Warranty: 2 years

Availability of spare parts: >10 years after last delivery Availability for re-order : >2 years after last delivery

Life time: >25.000 hours (70 % light transmission)

CE Conformity

The above mentioned lights are in accordance with EU-Directives 2006/95/EC (low voltage directive), 2004/108/EC (EMC-Directive), 2009/125/EC (Ecodesign requirements) and 2011/65/EU (RoHS-directive). The standards EN55015, EN 60598, EN 61000, EN 61347 and EN 61547 have been applied.

A declaration of CE Conformity will be supplied together with the product.

Brand Inside®

With our **Brand Inside®** guarantuee we guarantuee as one of the few suppliers, that only brand products are inside. "What is on the packaging will be also inside!". You will not find cloned products, "No-Name" products, Bquality, etc. from us.

Disposal

This product is in conformity with directive 2002/96/EU. Do not dispose this product with other houlehold waste. Instead, it should be disposed at a designated collection point for the recycling of waste electrical and electronic equipment.

Limitation of liability

Subject to modifications. Please ensure you are using the latest version of this datasheet.

DATASHEET

