



## OG33 Stadium light - Lumileds SMD

Aluminium casting, incl. driver. IP 65. With Lumileds (Philips) SDM 3030 LEDs / Meanwell driver. Optional with 10° beam angle (only with Cree / 110 Lm/W).

### Technical data

<b>LED Module producer</b>	Lumileds	<b>Dimmable</b>	not dimmable
<b>Technology</b>	SMD	<b>Appliance class</b>	I
<b>Heatsink</b>	Passive cooling	<b>IP class</b>	IP65
<b>CRI</b>	> 80	<b>Voltage</b>	230 V
<b>Surge current limit</b>	yes	<b>Power factor (PF)</b>	>0,90
<b>Type</b>	delayed switch on	<b>System efficiency</b>	170 Lm/W (A++)

Watt	A (mm)	B (mm)	C (mm)	Kg
300	Ø460	565	456	20,3
400	Ø460	565	456	20,3
450	Ø460	565	456	20,3
500	Ø460	565	456	20,3

<b>Beam angle</b>	120° - 30°
<b>Colour temperature</b>	830 - 840 - 857
<b>Product colour</b>	Black lacquered (Bk)

## DATASHEET



## Life time and warranty

Warranty:	2 years
Availability of spare parts:	>10 years after last delivery
Availability for re-order :	>2 years after last delivery
Life time:	>35.000 hours (70 % light transmission)

## CE Conformity

The above mentioned lights are in accordance with EU-Directives 2006/95/EC (low voltage directive), 2004/108/EC (EMC-Directive), 2009/125/EC (Ecodesign requirements) and 2011/65/EU (RoHS-directive). The standards EN55015, EN 60598, EN 61000, EN 61347 and EN 61547 have been applied.

A declaration of CE Conformity will be supplied together with the product.

## Brand Inside®

With our **Brand Inside®** guarantee we guarantee as one of the few suppliers, that only brand products are inside. „What is on the packaging will be also inside!“. You will not find cloned products, "No-Name" products, B-quality, etc. from us.

## Disposal

This product is in conformity with directive 2002/96/EU. Do not dispose this product with other household waste. Instead, it should be disposed at a designated collection point for the recycling of waste electrical and electronic equipment.

## Limitation of liability

Subject to modifications. Please ensure you are using the latest version of this datasheet.

# DATASHEET