



EPISTAR



OS11 Inground light - Epistar COB

Aluminium casting, incl. driver

Technical data

LED Module producer	Epistar	Dimmable	not dimmable
Technology	COB	Appliance class	I
Heatsink	Passive cooling	IP class	IP67
CRI	> 80	Voltage	230 V / 12 Volt
Surge current limit	yes	Power factor (PF)	>0,90
Type	delayed switch on	System efficiency	80 Lm/W (A+)

Version	Watt	A (mm)	B (mm)		Kg
A	4,50	Ø65	56	Ø56	0,5
RGB	9	Ø65	56	Ø56	0,5
A	10	Ø78	85	Ø75	0,5
RGB	12	Ø78	85	Ø75	0,5

Beam angle	30° - 45° - 60°
Colour temperature	830 - 840 - 860 - B - G - R - RGB - Y
Product colour	Black anodized (Bx)

DATASHEET



Life time and warranty

Warranty:	2 years
Availability of spare parts:	>10 years after last delivery
Availability for re-order :	>2 years after last delivery
Life time:	>35.000 hours (70 % light transmission)

CE Conformity

The above mentioned lights are in accordance with EU-Directives 2006/95/EC (low voltage directive), 2004/108/EC (EMC-Directive), 2009/125/EC (Ecodesign requirements) and 2011/65/EU (RoHS-directive). The standards EN55015, EN 60598, EN 61000, EN 61347 and EN 61547 have been applied.

A declaration of CE Conformity will be supplied together with the product.

Brand Inside®

With our **Brand Inside®** guarantee we guarantee as one of the few suppliers, that only brand products are inside. „What is on the packaging will be also inside!“. You will not find cloned products, "No-Name" products, B-quality, etc. from us.

Disposal

This product is in conformity with directive 2002/96/EU. Do not dispose this product with other household waste. Instead, it should be disposed at a designated collection point for the recycling of waste electrical and electronic equipment.

Limitation of liability

Subject to modifications. Please ensure you are using the latest version of this datasheet.

DATASHEET