





## PL07 Aluminium profile for flexible strips

Aluminium profile, with cover, with mounting clips. Complete set, 1.000 mm. For strips max. 12 mm width

#### **Technical data**

LED Module producer Technology Heatsink CRI Surge current limit Type Dimmable
Appliance class
IP class
Voltage
Power factor (PF)
System efficiency


**A (mm) B (mm) C (mm) Kg** 1000 19 19 0,25

Beam angle Colour temperature Product colour

Aluminium anodized (AI)

# DATASHEET









#### Life time and warranty

Warranty: 2 years

>10 years after last delivery Availability of spare parts: Availability for re-order : >2 years after last delivery

Life time:

### **CE Conformity**

The above mentioned lights are in accordance with EU-Directives 2006/95/EC (low voltage directive), 2004/108/EC (EMC-Directive), 2009/125/EC (Ecodesign requirements) and 2011/65/EU (RoHS-directive). The standards EN55015, EN 60598, EN 61000, EN 61347 and EN 61547 have been applied.

A declaration of CE Conformity will be supplied together with the product.

# Brand Inside®

With our Brand Inside® guarantuee we guarantuee as one of the few suppliers, that only brand products are inside. "What is on the packaging will be also inside!". You will not find cloned products, "No-Name" products, Bquality, etc. from us.

# **Disposal**

This product is in conformity with directive 2002/96/EU. Do not dispose this product with other houlehold waste. Instead, it should be disposed at a designated collection point for the recycling of waste electrical and electronic equipment.

## Limitation of liability

Subject to modifications. Please ensure you are using the latest version of this datasheet.

# DATASHEET

