



SQ41 Ceiling light - Cree COB

Aluminium casting, swivable and 350 degrees rotatable, incl. driver. High performance Cree LEDs, 100 Lm/Watt, 30 - 90 Watt, 1 - 3 heads, white lacquered.

Technical data

LED Module producer	Cree	Dimmable	not dimmable
Technology	COB	Appliance class	II
Heatsink	Passive cooling	IP class	IP40
CRI	>80	Voltage	230 V
Surge current limit	yes	Power factor (PF)	>0,90
Type	delayed switch on	System efficiency	100 Lm/W (A++)

Watt	A (mm)	B (mm)	C (mm)		Kg
1 x 30	189	189	138	170 x 170	1
2 x 30	350	189	138	335 x 170	1,9
3 x 30	510	189	138	495 x 170	2,8

Beam angle	30° - 45° - 60°
Colour temperature	830 - 840 - 850
Product colour	White lacquered (Wh)

DATASHEET



Life time and warranty

Warranty:	2 years
Availability of spare parts:	>10 years after last delivery
Availability for re-order :	>2 years after last delivery
Life time:	>35.000 hours (70 % light transmission)

CE Conformity

The above mentioned lights are in accordance with EU-Directives 2006/95/EC (low voltage directive), 2004/108/EC (EMC-Directive), 2009/125/EC (Ecodesign requirements) and 2011/65/EU (RoHS-directive). The standards EN55015, EN 60598, EN 61000, EN 61347 and EN 61547 have been applied.

A declaration of CE Conformity will be supplied together with the product.

Brand Inside®

With our **Brand Inside®** guarantee we guarantee as one of the few suppliers, that only brand products are inside. „What is on the packaging will be also inside!“. You will not find cloned products, "No-Name" products, B-quality, etc. from us.

Disposal

This product is in conformity with directive 2002/96/EU. Do not dispose this product with other household waste. Instead, it should be disposed at a designated collection point for the recycling of waste electrical and electronic equipment.

Limitation of liability

Subject to modifications. Please ensure you are using the latest version of this datasheet.

DATASHEET