



SX61 Ceiling light - Cree CRI 90+ COB

Aluminium casting, swivable, incl. driver. High performance Cree LEDs, 90 Lm/Watt, 7 - 40 Watt, optional dimmable. Cree CRI 90 - True White! white lacquered or aluminium anodized.

Technical data

LED Module producer	Cree CRI 90+	Dimmable	not dimmable
Technology	COB	Appliance class	II
Heatsink	Passive cooling	IP class	IP40
CRI	>90	Voltage	230 V
Surge current limit	yes	Power factor (PF)	>0,90
Type	delayed switch on	System efficiency	90 Lm/W (A+)

Watt	A (mm)	B (mm)		Kg
7	Ø90	67	Ø70	0,5
9	Ø90	67	Ø70	0,5
10	Ø90	67	Ø70	0,5
12	Ø90	67	Ø70	0,5
15	Ø109	77	Ø92	0,8
18	Ø109	77	Ø92	0,8
20	Ø138	108	Ø117	1
25	Ø138	108	Ø117	1
30	Ø162	118	Ø140	1,2
35	Ø162	118	Ø140	1,2
40	Ø162	118	Ø140	1,2

Beam angle	15° - 24° - 38° - 60°
Colour temperature	927 - 930 - 940 - 950
Product colour	Aluminium anodized (Al) - White lacquered (Wh)

DATASHEET



Life time and warranty

Warranty:	2 years
Availability of spare parts:	>10 years after last delivery
Availability for re-order :	>2 years after last delivery
Life time:	>35.000 hours (70 % light transmission)

CE Conformity

The above mentioned lights are in accordance with EU-Directives 2006/95/EC (low voltage directive), 2004/108/EC (EMC-Directive), 2009/125/EC (Ecodesign requirements) and 2011/65/EU (RoHS-directive). The standards EN55015, EN 60598, EN 61000, EN 61347 and EN 61547 have been applied.

A declaration of CE Conformity will be supplied together with the product.

Brand Inside®

With our **Brand Inside®** guarantee we guarantee as one of the few suppliers, that only brand products are inside. „What is on the packaging will be also inside!“. You will not find cloned products, "No-Name" products, B-quality, etc. from us.

Disposal

This product is in conformity with directive 2002/96/EU. Do not dispose this product with other household waste. Instead, it should be disposed at a designated collection point for the recycling of waste electrical and electronic equipment.

Limitation of liability

Subject to modifications. Please ensure you are using the latest version of this datasheet.

DATASHEET